Material Safety Data Sheet





Revision Number: 004.0 Issue date: 03/08/2013

PRODUCT AND COMPANY IDENTIFICATION

LOCTITE® 7452™ ACCELERATOR Product name:

TAK PAK®

Product type: Accelerator

Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 229769

18580 Item number: Region: **United States**

Contact information:

Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

*2 Physical state: Liquid **HEALTH:** Color: Clear, to, amber FLAMMABILITY: 3 Odor: Acetone PHYSICAL HAZARD: 0

Personal Protection: See MSDS Section 8

DANGER: EXTREMELY FLAMMABLE.

CAUSES EYE IRRITATION.

VAPOR MAY CAUSE FLASH FIRE. ASPIRATION HAZARD IF SWALLOWED.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation. Central nervous system depression, including dizziness,

drowsiness, fatigue, nausea, headache, unconsciousness.

Skin contact: May cause irritation due to defatting of the skin. Redness. Burns. Skin absorption is possible,

but harmful effects are not expected from this route of exposure under normal conditions of

handling and use.

Eye contact: Causes eye irritation. Exposure to vapor may cause tearing of the eyes, irritation and burning

sensation.

Indestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Central nervous

system depression, including dizziness, drowsiness, fatigue, nausea, headache,

unconsciousness.

Existing conditions aggravated by

exposure:

Liver disorders. Kidney disorders. Lung disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

IDH number: 229769 Product name: LOCTITE® 7452™ ACCELERATOR TAK PAK® Page 1 of 5

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Acetone	67-64-1	60 - 100
Benzenamine, N,N,4-trimethyl-	99-97-8	0.1 - 1

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

Flash point: -17 °C (1.4 °F) Tagliabue closed cup

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: 2.8 %
Flammable/Explosive limits - upper: 12.8 %

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures:Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: Vapors may accumulate in low or confined areas, travel considerable distance

to source of ignition, and flash back. Closed containers may rupture (due to

build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Vapors are heavier than air and may travel

along the ground or be moved by ventilation and subsequently ignited by heat, pilot lights or other ignition sources at locations distant from the material handling point. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed metal container until

ready for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m3) TWA	None	None
Benzenamine, N.N.4-trimethyl-	None	None	0.5 ppm TWA	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection:Goggles. Safety glasses with side-shields.Skin protection:Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Clear, to, amber Odor: Acetone Odor threshold: Not available. pH: not applicable

Vapor pressure: 185 mm hg (20 °C (68°F)) Approximately

Boiling point/range: 57 °C (134.6 °F)
Melting point/ range: Not available.
Specific gravity: 0.7926
Vapor density: 2 Approximately

Flash point: -17 °C (1.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

2.8 %

Not available.

1.9 (Ether = 1)

Soluble

Not available.

1.02 %; 80 g/l

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Not available.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
Benzenamine, N,N,4-trimethyl-	No	No	No

Hazardous components	Health Effects/Target Organs	
Acetone	Blood, Central nervous system, Irritant, Reproductive	
Benzenamine, N,N,4-trimethyl-	Mutagen, Allergen	

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Acetone
Hazard class or division: 3
Identification number: UN 1090
Packing group: II
DOT Reportable quantity: Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Acetone
Hazard class or division: 3
Identification number: UN 1090
Packing group: II

Exceptions: (Not more than 500 ml), May Qualify as Consumer Commodity, ID8000

Water Transportation (IMO/IMDG)

Proper shipping name: ACETONE
Hazard class or division: 3
Identification number: UN 1090
Packing group: II

Exceptions: Limited quantity (Not more than 1 L).

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimis
Fire, Immediate Health, Delayed Health
None above reporting de minimis

CERCLA Reportable quantity: Acetone (CAS# 67-64-1) 5,000 lbs. (2,270 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

IDH number: 229769 Product name: LOCTITE® 7452™ ACCELERATOR TAK PAK® Page 4 of 5

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

WHMIS hazard class: B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 229769 Product name: LOCTITE® 7452™ ACCELERATOR TAK PAK®